

### MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

### RECEIVED

By Carol Day at 1:50 pm, Sep 06, 2013

REPORT#7

ALCO SENSOR IV SN 03450		PRINTER SN 95.1111.053	)		DATE OF INSPECTION
LOCATION OF INSTRUME		) )	)		09/04/2013 TIME OF INSPECTION
501 FARAON ST. JO	01 FARAON ST. JOSEPH, MO			i	1930
ues where determined	mark in the box by .) Unmarked items	y each item it found to s must be corrected b	o be satisfactory or if op pefore using instrument,	perating within establi	shed limits. (Write in observed
DIGITAL READO	Л (ALL ELEMEN	TS OPERATIONAL)			
TEMPERATURE (	OF ALGO SENSOF	R (1 O-C - 40-C)			
PRINTER WORK	NG PROPERLY				•
TIME AND DATE	DISPLAYING PRO	PERLY			
BREATH ALCOHOL A	CCURACY STAN	DARDS			
SIMULATOR SOLI	JTION		⊠ compre	SSED ETHANOL-GA	S MIXTURE
STANDARD SUPP	LIER AIR GAS		LOT # AG300020	EXP. DATE	01/02/2015
SIMULATOR TEM	PERATURE (34'C	± 0.2'C)	SIMULATOR SN	SIMULA	ATOR EXP DATE
less. Check the box	ig a standard solu corresponding to t	ition. All three tests r lhe standard solution	being used, (PRINTOL	the standard value ar JT ATTACHED)	nd must have a spread of .00!
less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI	ng a standard solu corresponding to t DARD - MUST RE DARD - MUST RE	ition. All three tests r the standard solution AD BETWEEN 0.095 AD BETWEEN 0.038	must be within ±5% of t	ihe standard value ar JT ATTACHED) SIVE SIVE	nd must have a spread of ,00!
less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI	ng a standard solu corresponding to t DARD - MUST RE DARD - MUST RE	ition. All three tests r the standard solution AD BETWEEN 0.095 AD BETWEEN 0.076	nust be within ±5% of t being used. (PRINTOL 5% and 0.105% INCLUS 5% and 0.084% INCLUS	ihe standard value ar JT ATTACHED) SIVE SIVE	nd must have a spread of .00!
less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI	ng a standard solu corresponding to DARD - MUST RE DARD - MUST RE DARD - MUST RE	ition. All three tests r the standard solution AD BETWEEN 0.095 AD BETWEEN 0.038	nust be within ±5% of t being used. (PRINTOL 5% and 0.105% INCLUS 5% and 0.084% INCLUS	ihe standard value ar JT ATTACHED) SIVE SIVE	nd must have a spread of .00!
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE	ng a standard solu corresponding to DARD - MUST RE DARD - MUST RE DARD - MUST RE ERATING	ition. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.036 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO	must be within ±5% of the being used. (PRINTOL 5% and 0.105% INCLUS 3% and 0.084% INCLUS 5% and 0.042% INCLUS	the standard value ar JT ATTACHED) SIVE SIVE SIVE TEST 3098	
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI	ng a standard solu corresponding to DARD - MUST RE DARD - MUST RE DARD - MUST RE ERATING	ition. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.036 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO	must be within ±5% of the being used. (PRINTOL SW and 0.105% INCLUST and 0.084% INCLUST and 0.042% INCLUST AND COMPANAGES SINCOMPANAGES SINCOM	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.098  REFUSALS 8	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.098  REFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8  Ist any new parts and costablished limits (use of stablished limits)	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.	g a standard solucorresponding to to DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value ar JT ATTACHED) SIVE SIVE TEST 3098 CE THE LAST MAINT	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.	ag a standard solucorresponding to a DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value are IT ATTACHED) SIVE SIVE TEST 3098  CE THE LAST MAINT  (.1519) 7  ore the instrument to a	ENANCE REPORT:
Run three tests using less. Check the box 0.100% STANI 0.080% STANI 0.040% STANI 0.040% STANI 0.040% STANI 0.098  RFI DETECTOR OP NDICATE THE NUMBE DO NOT INCLUDE SEI REFUSALS 8	ag a standard solucorresponding to a DARD - MUST REDARD -	ation. All three tests rethe standard solution AD BETWEEN 0.096 AD BETWEEN 0.038 TEST 2 - ,098  ESTS IN THE FOLLO D TESTS) (.0509) 2	must be within ±5% of the being used. (PRINTOL of the being used. (PRINTOL of the being used. (PRINTOLUS) and 0.084% INCLUS of the being used. (10-14) 4	the standard value are IT ATTACHED) SIVE SIVE TEST 3098  CE THE LAST MAINT  (.1519) 7  ore the instrument to a	ENANCE REPORT:

Poplar Bluff, MO 63901

# Airgas.

Airgas Mid America (LABORATORY)

3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100

Fax: (314) 533-7328

### **Certificate of Analysis**

Customer Name Infoximeters, Inc.

2081 Craig Road St. Louis, Mo 63146 Test Date: 2-Jan-2013

Dear Sir,

This is your Cerlificate of Analysis:

Exp. Date

Cyl. Type

Component

Certified Concentration

1/2/2015

108

Ethanol Nitrogen 0.100 ± 2% BrAC (272 ppm)

Balance

Lot#

AG300201

Certification Traceable to N.I.S.T. RGM Ethanol Standards:

Serial No.	Concentration	Serial No.	Concentration
EB0010581	391.5 ppm	EB0010603	390,9 ppm
EB0010570	258.4 ppm	EB0010559	258.3 ppm
EB0010285	208.9 ppm	EB0010595	209.2 ppm
EB0010561	101.9 ppm	E80010562	104.9 ppm
EB0010681	53.0 ppm	EB0010579	52.4 ppm

**Analytical Method:** 

**NDIR** 

ISO 17025:2005 A2LA accredited. Certificate Number 2989.01

** ** ** *** *** *** *** *** *** *** *	The state of the s		STATE OF THE STATE	A COLOMBO COMPANION ORGANIZATION AND AND AND AND AND AND AND AND AND AN	等1. 人種的名词数 (2. ) 经期间的	# 1	
C) () — A sea of the first and the control of the c	The second state of the se	A many consistent measurement of the second sections of the section sections of the second section sections of the second sections of the section sections of the second sections of the second sections of the second section sections of the section sections of the section section sections of the section sectio	A STATE OF THE STA		1000 (中国) 1000 (1000 mm)	TOTAL SECTION STATE OF SECTION	
		The state of the s	Tearmor Names I.D.	1000年代の大学の大学の大学の大学の大学の大学の大学の大学の大学の大学の大学の大学の大学の	The second of th	The color of the	
	e in the second	Theretor Name: I.B.	COUNTY TO STATE OF THE STATE OF		100 / 100 /	THE RECORD STIRS  THE RECORD S	

## State of Missouri DEPARTMENT OF HEALTH



### PERMIT TYPE II



#### **SCOTT GARY**

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field repairs, and operate the following breath analyzer(s):

#### DATAMASTER; ALCO-SENSOR IV W/PRINTER

for the determination of the alcoholic content of blood from a sample of expired (alveolar) air, issued under the provisions of sections 577.020 through 577.041, RSMo 1986.

Date 08/03/2012	Wante
Number 220179	Director of State Public Health Laboratory
Expires <u>08/03/2014</u>	Margart T. Bruelly Director, Department of Health
MO 590-0771 (7-88)	Lab. 4 (R7-88)